

## Usage Guideline

# DTCC Usage Guideline Meeting Cancellation seev.002.001.10

## DTCC - US - PX - Meetings - SR 2025

This document describes a usage guideline restricting the base message **MX seev.002.001.10**. You can also consult [this information online](#).

Published by DTCC - Corporate Action Transformation and generated by [MyStandards](#).

17 March 2025

# Table of Contents

**Message Functionality** ..... 3

**1    Restriction summary** ..... 4

**2    Structure** ..... 5

**3    Guidelines** ..... 6

**4    Message Building Blocks** ..... 7

**5    Message Components** ..... 9

**6    Message Datatypes** ..... 57

**Legal Notices** ..... 78

## Message Functionality

### Overview

#### Scope

This message is sent to cancel a MeetingNotification message previously sent or to advise the cancellation of a meeting. It is sent by the party that sent the MeetingNotification message to the original Receiver.

#### Usage

The MeetingCancellation message may be used in two different situations. First, it may be sent to cancel a previously sent MeetingNotification message. In this case, the MessageCancellation building block must be filled in and the MeetingIdentification needs to be present. Second, it may be sent to advise that the meeting is cancelled. In this case only the MeetingIdentification needs to be present.

### Collection Description

#### Outline

The DTCC - US - PX - Meetings - SR 2025 / DTCC Usage Guideline Meeting Cancellation seev.002.001.10 message is composed of 4 building blocks

a. MeetingReference

Set of elements to allow the unambiguous identification of a meeting.

b. Security

Identification of the security for which the meeting was organised.

c. Reason

Justification for the cancellation.

d. SupplementaryData







Additional information that cannot be captured in the structured fields and/or any other specific block.









# 1 Restriction summary

This Usage Guideline restricts the seev.002.001.10 message.

Restriction Type	See page
Removed elements	8, 21, 23, 24, 26, 27, 29, 30, 30, 31, 45, 45, 45, 45, 46, 53, 53, 55, 65, 67, 67, 67, 68, 68, 68, 69
Make mandatory	n.a.
Reduce Multiplicity	n.a.
Ignore	n.a.
Text rules	20, 22, 23
Conditional rules	n.a.
Formal rules	n.a.
Fixed values	n.a.
Truncates	n.a.
Comments	n.a.
Annotations	n.a.
Changed datatypes	n.a.
Extensions	n.a.
Synonyms	8, 8, 23, 23, 23, 26, 65, 66

## 2 Structure

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below -  
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	<i>MeetingCancellationV10</i>	<MtgCxl>		[1..1]		
	<b>MeetingReference</b>	<MtgRef>		[1..1]		7
	MeetingIdentification	<MtgId>		[1..1]		22
	IssuerMeetingIdentification	<IssrMtgId>		[0..1]		23
	MeetingDateAndTime	<MtgDtAndTm>		[1..1]		23
	Type	<Tp>		[1..1]		23
	Classification	<Clssfctn>		[0..1]		24
	Location	<Lctn>		[0..5]		24
	Issuer	<Issr>		[0..1]		25
	<b>Security</b>	<Scty>		[1..200]		7
	FinancialInstrumentIdentification	<FinInstrmId>		[1..1]		54
	Position	<Pos>		[0..1000]		54
	<b>Reason</b>	<Rsn>		[1..1]		8
	CancellationReasonCode	<CxlRsnCd>		[0..1]		21
	CancellationReason	<CxlRsn>		[0..1]		22
	<b>SupplementaryData</b>	<SplntryData>		[0..*]		8
	PlaceAndName	<PlcAndNm>		[0..1]		56
	Envelope	<Envlp>		[1..1]		56

## 3 Guidelines

### 1. Cancellation1Guideline

It is recommended that a meeting is cancelled with the use of MeetingReference/MeetingIdentification, MeetingReference/Type and Security and Reason only. It is recommended that optional elements are not used.

## 4 Message Building Blocks

**Note** The following chapter identifies the building blocks of the DTCC - US - PX - Meetings - SR 2025 / DTCC Usage Guideline Meeting Cancellation seev.002.001.10 message definition.







### 4.1 MeetingReference





*XML Tag:* MtgRef

*Presence:* [1..1]

*Definition:* Set of elements to allow the unambiguous identification of a meeting.

The **MtgRef** block contains the following elements (see datatype "[MeetingReference10](#)" on page 22 for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	MeetingIdentification	<MtgId>		[1..1]		22
	IssuerMeetingIdentification	<IssrMtgId>		[0..1]		23
	MeetingDateAndTime	<MtgDtAndTm>		[1..1]		23
	Type	<Tp>		[1..1]		23
	Classification	<Clssfctn>		[0..1]		24
	Location	<Lctn>		[0..5]		24
	Issuer	<Issr>		[0..1]		25







### 4.2 Security


*XML Tag:* Scty

*Presence:* [1..200]

*Definition:* Identification of the security for which the meeting was organised.

The **Scty** block contains the following elements (see datatype "[SecurityPosition23](#)" on page 53 for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstrumentIdentification	<FinInstrmId>		[1..1]		54
	Position	<Pos>		[0..1000]		54

## Usage Guideline details

- on **seev.002.001.10/Security**  
**Synonym (DTCC):** Event Security ID Type
- on **seev.002.001.10/Security**  
**Synonym (DTCC):** Event Security ID







## 4.3 Reason


*XML Tag:* Rsn

*Presence:* [1..1]

*Definition:* Justification for the cancellation.

The **Rsn** block contains the following elements (see datatype "[MeetingCancellationReason2](#)" on page 21 for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CancellationReasonCode	<CxlRsnCd>		[0..1]		21
	CancellationReason	<CxlRsn>		[0..1]		22







## 4.4 SupplementaryData

*XML Tag:* SplmtryData

*Presence:* [0..\*]

*Definition:* Additional information that cannot be captured in the structured fields and/or any other specific block.

The **SplmtryData** block contains the following elements (see datatype "[SupplementaryData1](#)" on page 55 for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	PlaceAndName	<PlcAndNm>		[0..1]		56
	Envelope	<Envlp>		[1..1]		56

## Usage Guideline details

- This element([seev.002.001.10/SupplementaryData](#)) is removed.









## 5 Message Components

**Note** The following chapter identifies the message components.

### 5.1 DateAndPlaceOfBirth2

*Definition:* Date and place of birth of a person.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BirthDate	<BirthDt>		[1..1]		9
	ProvinceOfBirth	<PrvcOfBirth>		[0..1]		9
	CityOfBirth	<CityOfBirth>		[0..1]		9
	CountryOfBirth	<CtryOfBirth>		[0..1]		9

**Used in element(s)**

"DateAndPlaceOfBirth" on page 36, "DateAndPlaceOfBirth" on page 39

#### 5.1.1 BirthDate

*XML Tag:* BirthDt

*Presence:* [1..1]

*Definition:* Date on which a person is born.

*Datatype:* "ISODate" on page 61

#### 5.1.2 ProvinceOfBirth

*XML Tag:* PrvcOfBirth

*Presence:* [0..1]

*Definition:* Province where a person was born.

*Datatype:* "Max35Text" on page 64

#### 5.1.3 CityOfBirth

*XML Tag:* CityOfBirth

*Presence:* [0..1]

*Definition:* City where a person was born.

*Datatype:* "Max35Text" on page 64

#### 5.1.4 CountryOfBirth

*XML Tag:* CtryOfBirth

*Presence:* [0..1]

*Definition:* Country where a person was born.

*Datatype:* "CountryCode" on page 58

## 5.2 EligiblePosition21

*Definition:* Information about a securities position and rights holders.

❌ Removed - ❌ Partial Removed - ❖ Ignored - ❖ Partial Ignored - ⚠ Details below -  
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AccountIdentification	<AcctId>		[0..1]		11
	BlockChainAddressOrWallet	<BlckChainAdrOrWllt>		[0..1]		11
	AccountOwner	<AcctOwnr>		[0..1]		11
	HoldingBalance	<HldgBal>		[0..15]		12
	RightsHolder	<RghtsHldr>		[0..250]		12

### Rules

#### R2 HoldingBalanceTypeRule

In all occurrences of HoldingBalance, one and only one BalanceType may be ELIG (Eligible).

Error handling:

- *Error severity:* Fatal
- *Error Code:*
- *Error Text:*

#### R3 AccountIdentificationOrBlockChainAddress1Rule ✓

Either AccountIdentification or BlockChainAddressOrWallet must be present but not both.

Error handling:

- *Error severity:* Warning
- *Error Code:* X00551
- *Error Text:* Invalid message contents for SafekeepingAccount or BlockchainAddressOrWallet. Only one of both must be present.

#### R4 AccountIdentificationOrBlockChainAddress2Rule ✓

If BlockChainAddressOrWallet is present then AccountIdentification must be absent.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00565

- *Error Text:* Invalid message contents for SafekeepingAccount or BlockchainAddressOrWallet. Only one of both must be present.

#### **R5 AccountIdentificationOrBlockchainAddress3Rule ✓**

If AccountIdentification is present, then BlockChainAddressOrWallet must be absent.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00566
- *Error Text:* Invalid message contents for SafekeepingAccount or BlockchainAddressOrWallet. Only one of both must be present.

#### **Guidelines**

##### **1. RightsHolderMultiplicity1Guideline**

It is recommended that RightsHolder is only present more than once if there is joint ownership.

#### **Used in element(s)**

"Position" on page 54

## **5.2.1 AccountIdentification**

*XML Tag:* AcctId

*Presence:* [0..1]

*Definition:* Identification of the securities account.

*Datatype:* "Max35Text" on page 64

## **5.2.2 BlockchainAddressOrWallet**

*XML Tag:* BlckChainAdrOrWllt

*Presence:* [0..1]

*Definition:* Blockchain address or wallet where digital assets are maintained. This is the equivalent of safekeeping account for digital assets.

*Datatype:* "Max140Text" on page 62







## **5.2.3 AccountOwner**

*XML Tag:* AcctOwnr

*Presence:* [0..1]

*Definition:* Party that legally owns the account.

The **AcctOwnr** block contains the following elements (see datatype "PartyIdentification231Choice" on page 34 for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	LegalPerson	<LglPrsn>	{Or	[1..1]		34
	NaturalPerson	<NtrlPrsn>	Or}	[1..*]		34







## 5.2.4 HoldingBalance

*XML Tag:* HldgBal

*Presence:* [0..15]

*Definition:* Net position of a segregated holding of a single security within the overall position held in a securities account, for example, sub-balance per status.

The **HldgBal** block contains the following elements (see datatype "HoldingBalance14" on page 17 for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Balance	<Bal>		[1..1]		17
	BalanceType	<BalTp>		[1..1]		18
	SafekeepingPlace	<SfkpgPlc>		[0..1]		18
	Date	<Dt>		[0..1]		18







## 5.2.5 RightsHolder

*XML Tag:* RgthsHldr

*Presence:* [0..250]

*Definition:* Owner of the voting rights.







The **RgthsHldr** block contains the following elements (see datatype "PartyIdentification246Choice" on page 37 for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	LegalPerson	<LglPrsn>	{Or	[1..1]		37
	NaturalPerson	<NtrlPrsn>	Or}	[1..*]		37

## 5.3 FinancialInstrumentQuantity45Choice

*Definition:* Choice between formats for the quantity of security.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Unit	<Unit>	{Or	[1..1]		13
	FaceAmount	<FaceAmt>	Or	[1..1]		13
	DigitalTokenUnit	<DgtlTknUnit>	Or}	[1..1]		13

**Rules****R6 DigitalTokenUnitUsageRule**

DigitalTokenUnit format may only be used for instruments identified with a digital token identifier.

Error handling: Undefined

**Used in element(s)**

"Quantity" on page 55

### 5.3.1 Unit

XML Tag: Unit

Presence: [1..1]

Definition: Quantity expressed as a number, for example, a number of shares.

Datatype: "DecimalNumber" on page 59

### 5.3.2 FaceAmount

XML Tag: FaceAmt

Presence: [1..1]

Definition: Quantity expressed as an amount representing the face amount, that is, the principal, of a debt instrument.

Datatype: "ImpliedCurrencyAndAmount" on page 61

### 5.3.3 DigitalTokenUnit

XML Tag: DgtlTknUnit







Presence: [1..1]

Definition: Quantity of digital tokens expressed as a number, for example, a number of blockchain tokens.

Datatype: "Max30DecimalNumber" on page 63

## 5.4 GenericIdentification13

Definition: Information related to an identification, for example, party identification or account identification.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - 
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		14
	SchemeName	<SchmeNm>		[0..1]		14
	Issuer	<Issr>		[1..1]		14

**Used in element(s)**

"Proprietary" on page 20, "Proprietary" on page 25

## 5.4.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification assigned by an institution.

Datatype: "Max4AlphaNumericText" on page 64

## 5.4.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

Datatype: "Max35Text" on page 64

## 5.4.3 Issuer

XML Tag: Issr







Presence: [1..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 64

## 5.5 GenericIdentification30

Definition: Information related to an identification, for example, party identification or account identification.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - 
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		15
	Issuer	<Issr>		[1..1]		15
	SchemeName	<SchmeNm>		[0..1]		15

**Used in element(s)**

"Proprietary" on page 19, "Type" on page 16

## 5.5.1 Identification

*XML Tag:* Id

*Presence:* [1..1]

*Definition:* Proprietary information, often a code, issued by the data source scheme issuer.

*Datatype:* "Exact4AlphaNumericText" on page 59

## 5.5.2 Issuer

*XML Tag:* Issr

*Presence:* [1..1]

*Definition:* Entity that assigns the identification.

*Datatype:* "Max35Text" on page 64

## 5.5.3 SchemeName

*XML Tag:* SchmeNm

*Presence:* [0..1]

*Definition:* Short textual description of the scheme.

*Datatype:* "Max35Text" on page 64

## 5.6 GenericIdentification36

*Definition:* Identification using a proprietary scheme.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -  
 📌 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		15
	Issuer	<Issr>		[1..1]		16
	SchemeName	<SchmeNm>		[0..1]		16

**Used in element(s)**

"ProprietaryIdentification" on page 30, "ProprietaryIdentification" on page 32

## 5.6.1 Identification

*XML Tag:* Id

*Presence:* [1..1]

*Definition:* Proprietary information, often a code, issued by the data source scheme issuer.

Datatype: "Max35Text" on page 64

## 5.6.2 Issuer

XML Tag: Issr

Presence: [1..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 64

## 5.6.3 SchemeName

XML Tag: SchmeNm







Presence: [0..1]

Definition: Short textual description of the scheme.

Datatype: "Max35Text" on page 64

## 5.7 GenericIdentification78

Definition: Identification expressed as a proprietary type and narrative description.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[1..1]		16
	Identification	<Id>		[0..1]		17

Used in element(s)

"Proprietary" on page 50







### 5.7.1 Type

XML Tag: Tp

Presence: [1..1]

Definition: Proprietary information, often a code, issued by the data source scheme issuer.

The **Tp** block contains the following elements (see datatype "GenericIdentification30" on page 14 for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		15
	Issuer	<Issr>		[1..1]		15



Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	SchemeName	<SchmeNm>		[0..1]		15

## 5.7.2 Identification

*XML Tag:* Id







*Presence:* [0..1]

*Definition:* Name or number assigned by an entity to enable recognition of that entity, for example, account identifier.

*Datatype:* "Max35Text" on page 64

## 5.8 HoldingBalance14

*Definition:* Net position of a segregated holding of a single security within the overall position held in the securities account, for example, sub-balance per status.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below -  
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Balance	<Bal>		[1..1]		17
	BalanceType	<BalTp>		[1..1]		18
	SafekeepingPlace	<SfkpgPlc>		[0..1]		18
	Date	<Dt>		[0..1]		18

**Used in element(s)**

"HoldingBalance" on page 12







### 5.8.1 Balance

*XML Tag:* Bal

*Presence:* [1..1]

*Definition:* Total quantity of financial instrument for the referenced holding.

The **Bal** block contains the following elements (see datatype "SignedQuantityFormat14" on page 55 for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below -  
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ShortLongPosition	<ShrtLngPos>		[1..1]		55
	Quantity	<Qty>		[1..1]		55

## 5.8.2 BalanceType

XML Tag: BalTp

Presence: [1..1]

**Definition:** Reason a security is not available or additional information about the financial instrument for which the balance is given, for example, unregistered, registered in nominee name.

**Datatype:** "SecuritiesEntryType2Code" on page 72

## 5.8.3 SafekeepingPlace

XML Tag: SfkpgPlc

Presence: [0..1]

**Definition:** Place where the securities are safe-kept, physically or notionally. This place can be, for example, a local custodian, a Central Securities Depository (CSD) or an International Central Securities Depository (ICSD).

The **SfkpgPlc** block contains the following elements (see datatype "SafekeepingPlaceFormat42Choice" on page 48 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -  
**M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>	{Or	[1..1]		49
	Country	<Ctry>	Or	[1..1]		49
	DigitalLedgerIdentification	<DgtlLdgrld>	Or	[1..1]		49
	TypeAndIdentification	<TpAndId>	Or	[1..1]		49
	Proprietary	<Prtry>	Or}	[1..1]		50

## 5.8.4 Date

XML Tag: Dt

Presence: [0..1]

**Definition:** Date of the entitlement.

**Datatype:** "ISODate" on page 61

## 5.9 IdentificationSource3Choice

**Definition:** Choice between source of identification of a financial instrument.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -  
**M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		19

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Proprietary	<Prtry>	Or}	[1..1]		19

Used in element(s)

["Type" on page 29](#)

## 5.9.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Unique and unambiguous identification source, as assigned via a pre-determined code list.

Datatype: ["ExternalFinancialInstrumentIdentificationType1Code" on page 59](#)

## 5.9.2 Proprietary

XML Tag: Prtry






Presence: [1..1]


Definition: Unique and unambiguous identification source using a proprietary identification scheme.

Datatype: ["Max35Text" on page 64](#)

## 5.10 IdentificationType45Choice

Definition: Choice between a code and a data source scheme to specify the type of natural person identification.

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -

 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		19
	Proprietary	<Prtry>	Or}	[1..1]		19

Used in element(s)

["IdentificationType" on page 28](#)

### 5.10.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Type of identification expressed as a code.

Datatype: ["TypeOfIdentification4Code" on page 76](#)

### 5.10.2 Proprietary

*XML Tag:* Prtry

*Presence:* [1..1]

*Definition:* Type of identification expressed as a proprietary code.

The **Prtry** block contains the following elements (see datatype "[GenericIdentification30](#)" on page 14 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -  
**M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		15
	Issuer	<Issr>		[1..1]		15
	SchemeName	<SchmeNm>		[0..1]		15

## 5.11 MeetingCancellationReason1Choice

*Definition:* Choice of meeting cancellation reason.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -  
**M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]	⚠	20
	Proprietary	<Prtry>	Or}	[1..1]	🚫	20

**Used in element(s)**

["CancellationReasonCode"](#) on page 21

### 5.11.1 Code

*XML Tag:* Cd

*Presence:* [1..1]

*Definition:* Specifies the reason for cancelling a meeting in coded form.

*Datatype:* "[MeetingCancellationReason2Code](#)" on page 65

**Usage Guideline details**

- on [seev.002.001.10/Reason/CancellationReasonCode/Code](#)
  - **DTCC Market Practice Rule:**

Derived from DTC Event Status.







### 5.11.2 Proprietary

*XML Tag:* Prtry

*Presence:* [1..1]

*Definition:* Specifies the reason for cancelling a meeting in free text form.

The **Prtry** block contains the following elements (see datatype "[GenericIdentification13](#)" on page 13 for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]







Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		14
	SchemeName	<SchmeNm>		[0..1]		14
	Issuer	<Issr>		[1..1]		14


#### Usage Guideline details

- This element([see v.002.001.10/Reason/CancellationReasonCode/Proprietary](#)) is removed.

## 5.12 MeetingCancellationReason2

*Definition:* Specifies the reason for cancelling a meeting.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CancellationReasonCode	<CxIRsnCd>		[0..1]		21
	CancellationReason	<CxIRsn>		[0..1]		22

#### Used in element(s)

"Reason" on page 8







### 5.12.1 CancellationReasonCode

*XML Tag:* CxIRsnCd

*Presence:* [0..1]

*Definition:* Reason for cancelling a meeting.

The **CxIRsnCd** block contains the following elements (see datatype "[MeetingCancellationReason1Choice](#)" on page 20 for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or}	[1..1]	⚠	20
	Proprietary	<Prtry>	Or}	[1..1]	🚫	20

## 5.12.2 CancellationReason

*XML Tag:* CxlRsn

*Presence:* [0..1]

*Definition:* Provides more information on the reason for cancelling a meeting in free format form.

*Datatype:* "Max140Text" on page 62

### Usage Guideline details

- on seev.002.001.10/Reason/CancellationReason

- DTCC Market Practice Rule:

First 140 characters of the comment regarding a cancellation / deletion reason.

## 5.13 MeetingReference10

*Definition:* Identification of a meeting.

🚫 Removed - 🚫 Partial Removed - ⬡ Ignored - ⬡ Partial Ignored - ⚠ Details below -

📌 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	MeetingIdentification	<MtglId>		[1..1]	⚠	22
	IssuerMeetingIdentification	<IssrMtglId>		[0..1]	🚫	23
	MeetingDateAndTime	<MtglDtAndTm>		[1..1]	⚠	23
	Type	<Tp>		[1..1]		23
	Classification	<Clssfctn>		[0..1]		24
	Location	<Lctn>		[0..5]	🚫	24
	Issuer	<Issr>		[0..1]		25

### Used in element(s)

"MeetingReference" on page 7

## 5.13.1 MeetingIdentification

*XML Tag:* MtglId

*Presence:* [1..1]

*Definition:* Identification assigned to the general meeting by the party that provides the meeting notification. It must be unique to the party providing the notification.

*Datatype:* ["Max35Text" on page 64](#)

#### Usage Guideline details

- on [seev.002.001.10/MeetingReference/MeetingIdentification](#)
  - **DTCC Market Practice Rule:**

Mapped from CA Event ID.

## 5.13.2 IssuerMeetingIdentification

*XML Tag:* IssrMtgId

*Presence:* [0..1]

*Definition:* Identification assigned to the meeting by the issuer. It must be unique for the issuer.

*Datatype:* ["Max35Text" on page 64](#)

#### Usage Guideline details

- This element([seev.002.001.10/MeetingReference/IssuerMeetingIdentification](#)) is removed.

## 5.13.3 MeetingDateAndTime

*XML Tag:* MtgDtAndTm

*Presence:* [1..1]

*Definition:* Date and time at which the meeting will take place.

*Datatype:* ["ISODateTime" on page 61](#)

#### Usage Guideline details

- on [seev.002.001.10/MeetingReference/MeetingDateAndTime](#)  
**Synonym (DTCC):** Meeting Date
- on [seev.002.001.10/MeetingReference/MeetingDateAndTime](#)  
**Synonym (DTCC):** Meeting Time Zone
- on [seev.002.001.10/MeetingReference/MeetingDateAndTime](#)  
**Synonym (DTCC):** Meeting Time

## 5.13.4 Type

*XML Tag:* Tp

*Presence:* [1..1]

*Definition:* Type of meeting for which instructions are sent.

*Datatype:* "MeetingType4Code" on page 66

## 5.13.5 Classification

*XML Tag:* Clssfctn

*Presence:* [0..1]

*Definition:* Classification type of the meeting.

The **Clssfctn** block contains the following elements (see datatype "MeetingTypeClassification2Choice" on page 25 for details)

🚫 Removed - 🚫 Partial Removed - ⬢ Ignored - ⬢ Partial Ignored - ⚠ Details below -  
**M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or}	[1..1]		25
	Proprietary	<Prtry>	Or}	[1..1]	🚫	25

## 5.13.6 Location

*XML Tag:* Lctn

*Presence:* [0..5]

*Definition:* Place of the company meeting for the scheduled meeting date.

The **Lctn** block contains the following elements (see datatype "PostalAddress1" on page 44 for details)

🚫 Removed - 🚫 Partial Removed - ⬢ Ignored - ⬢ Partial Ignored - ⚠ Details below -  
**M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]	🚫	44
	AddressLine	<AdrLine>		[0..5]	🚫	45
	StreetName	<StrtNm>		[0..1]	🚫	45
	BuildingNumber	<BldgNb>		[0..1]	🚫	45
	PostCode	<PstCd>		[0..1]	🚫	45
	TownName	<TwnNm>		[0..1]		46
	CountrySubDivision	<CtrySubDvsn>		[0..1]		46
	Country	<Ctry>		[1..1]		46

### Usage Guideline details

- This element(seev.002.001.10/MeetingReference/Location) is removed.









## 5.13.7 Issuer




*XML Tag:* Issr

*Presence:* [0..1]

*Definition:* Institution that is the issuer of the security to which the meeting applies.







The **Issr** block contains the following elements (see datatype "[PartyIdentification129Choice](#)" on page 29 for details)


 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AnyBIC	<AnyBIC>	{Or	[1..1]		29
	ProprietaryIdentification	<PrtryId>	Or	[1..1]		30
	NameAndAddress	<NmAndAdr>	Or	[1..1]		30
	LEI	<LEI>	Or}	[1..1]		31

## 5.14 MeetingTypeClassification2Choice

*Definition:* Choice of meeting type classification.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		25
	Proprietary	<Prtry>	Or}	[1..1]		25

**Used in element(s)**

["Classification"](#) on page 24

### 5.14.1 Code

*XML Tag:* Cd

*Presence:* [1..1]

*Definition:* Type of meeting expressed as a code.

*Datatype:* "[MeetingTypeClassification2Code](#)" on page 68

### 5.14.2 Proprietary

*XML Tag:* Prtry

*Presence:* [1..1]

*Definition:* Type of meeting expressed as a proprietary code.

The **Prtry** block contains the following elements (see datatype "[GenericIdentification13](#)" on page 13 for details)

Removed - Partial Removed - Ignored - Partial Ignored - Details below -  
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		14
	SchemeName	<SchmeNm>		[0..1]		14
	Issuer	<Issr>		[1..1]		14

#### Usage Guideline details

- This element(seev.002.001.10/MeetingReference/Classification/Proprietary) is removed.

## 5.15 NameAndAddress5

*Definition:* Information that locates and identifies a party.

Removed - Partial Removed - Ignored - Partial Ignored - Details below -  
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[1..1]		26
	Address	<Adr>		[0..1]		26

#### Used in element(s)

"NameAndAddress" on page 30

### 5.15.1 Name

*XML Tag:* Nm

*Presence:* [1..1]

*Definition:* Name by which a party is known and which is usually used to identify that party.

*Datatype:* "[Max350Text](#)" on page 63

#### Usage Guideline details

- on seev.002.001.10/MeetingReference/Issuer/NameAndAddress/Name  
 Synonym (Issuer Description): DTCC







### 5.15.2 Address

*XML Tag:* Adr

*Presence:* [0..1]

*Definition:* Postal address of the party.

The **Adr** block contains the following elements (see datatype "[PostalAddress1](#)" on page 44 for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]







Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		44
	AddressLine	<AdrLine>		[0..5]		45
	StreetName	<StrtNm>		[0..1]		45
	BuildingNumber	<BldgNb>		[0..1]		45
	PostCode	<PstCd>		[0..1]		45
	TownName	<TwnNm>		[0..1]		46
	CountrySubDivision	<CtrySubDvsn>		[0..1]		46
	Country	<Ctry>		[1..1]		46

#### Usage Guideline details

- This element([see v.002.001.10/MeetingReference/Issuer/NameAndAddress/Address](#)) is removed.

## 5.16 NaturalPersonIdentification1

*Definition:* Identification number and identification type of a natural person.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		27
	IdentificationType	<IdTp>		[0..1]		28

#### Used in element(s)

"[Identification](#)" on page 36, "[Identification](#)" on page 39

### 5.16.1 Identification

*XML Tag:* Id

*Presence:* [1..1]

*Definition:* Natural person local identification.

Datatype: "Max35Text" on page 64

## 5.16.2 IdentificationType

XML Tag: IdTp

Presence: [0..1]

Definition: Type of local identification for a natural person.

The **IdTp** block contains the following elements (see datatype "IdentificationType45Choice" on page 19 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -  
**M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		19
	Proprietary	<Prtry>	Or}	[1..1]		19

## 5.17 OtherIdentification1

Definition: Other accepted financial instrument's identification than ISIN.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -  
**M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		28
	Suffix	<Sfx>		[0..1]	🚫	28
	Type	<Tp>		[1..1]		29

Used in element(s)

"OtherIdentification" on page 53

## 5.17.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification of a security.

Datatype: "Max35Text" on page 64

## 5.17.2 Suffix

XML Tag: Sfx

Presence: [0..1]

Definition: Identifies the suffix of the security identification.

Datatype: "Max16Text" on page 62

#### Usage Guideline details

- This element(seev.002.001.10/Security/FinancialInstrumentIdentification/OtherIdentification/Suffix) is removed.







## 5.17.3 Type

XML Tag: Tp

Presence: [1..1]

Definition: Type of the identification.







The **Tp** block contains the following elements (see datatype "IdentificationSource3Choice" on page 18 for details)




 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		19
	Proprietary	<Prtry>	Or}	[1..1]		19

## 5.18 PartyIdentification129Choice

Definition: Choice between different formats for the identification of a party.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AnyBIC	<AnyBIC>	{Or	[1..1]		29
	ProprietaryIdentification	<PrtryId>	Or	[1..1]		30
	NameAndAddress	<NmAndAdr>	Or	[1..1]		30
	LEI	<LEI>	Or}	[1..1]		31

Used in element(s)

"Issuer" on page 25

### 5.18.1 AnyBIC

XML Tag: AnyBIC

Presence: [1..1]

**Definition:** Code allocated to a financial or non-financial institution by the ISO 9362 Registration Authority, as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

**Datatype:** "AnyBICDec2014Identifier" on page 58

#### Usage Guideline details

- This element(seev.002.001.10/MeetingReference/Issuer/AnyBIC) is removed.







## 5.18.2 ProprietaryIdentification

**XML Tag:** PrtryId

**Presence:** [1..1]

**Definition:** Unique and unambiguous identifier, as assigned to a financial institution using a proprietary identification scheme.

The **PrtryId** block contains the following elements (see datatype "GenericIdentification36" on page 15 for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		15
	Issuer	<Issr>		[1..1]		16
	SchemeName	<SchmeNm>		[0..1]		16

#### Usage Guideline details

- This element(seev.002.001.10/MeetingReference/Issuer/ProprietaryIdentification) is removed.







## 5.18.3 NameAndAddress



**XML Tag:** NmAndAdr

**Presence:** [1..1]

**Definition:** Name and address of a party.

The **NmAndAdr** block contains the following elements (see datatype "NameAndAddress5" on page 26 for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[1..1]		26
	Address	<Adr>		[0..1]		26

## 5.18.4 LEI

*XML Tag:* LEI

*Presence:* [1..1]

*Definition:* Legal entity identification of the party.







*Datatype:* ["LEIIdentifier" on page 62](#)

### Usage Guideline details

- This element([seev.002.001.10/MeetingReference/Issuer/LEI](#)) is removed.

## 5.19 PartyIdentification198Choice

*Definition:* Identification of a party.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NationalRegistrationNumber	<NtlRegnNb>	{Or	[1..1]		31
	LEI	<LEI>	Or	[1..1]		31
	AnyBIC	<AnyBIC>	Or	[1..1]		31
	ClientIdentification	<ClntId>	Or	[1..1]		32
	ProprietaryIdentification	<PrtryId>	Or}	[1..1]		32

### Used in element(s)

["Identification" on page 33](#), ["Identification" on page 41](#)

### 5.19.1 NationalRegistrationNumber

*XML Tag:* NtlRegnNb

*Presence:* [1..1]

*Definition:* Number assigned by a national registration authority to an entity.

*Datatype:* ["Max35Text" on page 64](#)

### 5.19.2 LEI

*XML Tag:* LEI

*Presence:* [1..1]

*Definition:* Legal entity identifier of the party.

*Datatype:* ["LEIIdentifier" on page 62](#)

### 5.19.3 AnyBIC

*XML Tag:* AnyBIC

*Presence:* [1..1]

*Definition:* Code allocated to a financial or non-financial institution by the ISO 9362 Registration Authority, as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

*Datatype:* "AnyBICDec2014Identifier" on page 58

## 5.19.4 ClientIdentification

*XML Tag:* ClntId

*Presence:* [1..1]

*Definition:* Unique and unambiguous identification of the client's counterparty.

*Datatype:* "Max50Text" on page 64

## 5.19.5 ProprietaryIdentification

*XML Tag:* PrtryId

*Presence:* [1..1]

*Definition:* Unique and unambiguous identifier, as assigned to a financial institution using a proprietary identification scheme.

The **PrtryId** block contains the following elements (see datatype "GenericIdentification36" on page 15 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -  
**M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		15
	Issuer	<Issr>		[1..1]		16
	SchemeName	<SchmeNm>		[0..1]		16

## 5.20 PartyIdentification221

*Definition:* Identification of a party.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -  
**M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NameAndAddress	<NmAndAdr>		[1..1]		33
	EmailAddress	<EmailAdr>		[0..1]		33
	Identification	<Id>		[1..1]		33



Used in element(s)

["LegalPerson" on page 34](#)







## 5.20.1 NameAndAddress

XML Tag: NmAndAdr

Presence: [1..1]

Definition: Name and address of the party.

The **NmAndAdr** block contains the following elements (see datatype ["PersonName2" on page 42](#) for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[1..1]		42
	Address	<Adr>		[0..1]		42

## 5.20.2 EmailAddress

XML Tag: EmailAdr

Presence: [0..1]

Definition: Address for electronic mail (e-mail).

Datatype: ["Max256Text" on page 63](#)







## 5.20.3 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification of the party.

The **Id** block contains the following elements (see datatype ["PartyIdentification198Choice" on page 31](#) for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NationalRegistrationNumber	<NtlRegnNb>	{Or	[1..1]		31
	LEI	<LEI>	Or	[1..1]		31
	AnyBIC	<AnyBIC>	Or	[1..1]		31
	ClientIdentification	<ClnId>	Or	[1..1]		32
	ProprietaryIdentification	<PrtryId>	Or}	[1..1]		32

## 5.21 PartyIdentification231Choice

*Definition:* Identification of a party.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -  
**M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	LegalPerson	<LglPrsn>	{Or	[1..1]		34
	NaturalPerson	<NtrlPrsn>	Or}	[1..*]		34

**Used in element(s)**

"AccountOwner" on page 11

### 5.21.1 LegalPerson

*XML Tag:* LglPrsn

*Presence:* [1..1]

*Definition:* Legal entity.

The **LglPrsn** block contains the following elements (see datatype "PartyIdentification221" on page 32 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -  
**M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NameAndAddress	<NmAndAdr>		[1..1]		33
	EmailAddress	<EmailAdr>		[0..1]		33
	Identification	<Id>		[1..1]		33

### 5.21.2 NaturalPerson

*XML Tag:* NtrlPrsn

*Presence:* [1..\*]

*Definition:* Private person.

The **NtrlPrsn** block contains the following elements (see datatype "PartyIdentification238" on page 35 for details)







🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -  
**M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NameAndAddress	<NmAndAdr>		[1..1]		35
	EmailAddress	<EmailAdr>		[0..1]		35

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		36
	Nationality	<Ntlty>		[0..1]		36
	DateAndPlaceOfBirth	<DtAndPlcOfBirth>		[0..1]		36

## 5.22 PartyIdentification238

*Definition:* Identification of a party.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NameAndAddress	<NmAndAdr>		[1..1]		35
	EmailAddress	<EmailAdr>		[0..1]		35
	Identification	<Id>		[1..1]		36
	Nationality	<Ntlty>		[0..1]		36
	DateAndPlaceOfBirth	<DtAndPlcOfBirth>		[0..1]		36

Used in element(s)

"NaturalPerson" on page 34







### 5.22.1 NameAndAddress

*XML Tag:* NmAndAdr

*Presence:* [1..1]

*Definition:* Name and address of the party.

The **NmAndAdr** block contains the following elements (see datatype "PersonName3" on page 43 for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NamePrefix	<NmPrfx>		[0..1]		43
	FirstName	<FrstNm>		[1..1]		43
	Surname	<Snm>		[1..1]		43
	Address	<Adr>		[0..1]		43

### 5.22.2 EmailAddress

*XML Tag:* EmailAdr

*Presence:* [0..1]

*Definition:* Address for electronic mail (e-mail).

*Datatype:* "Max256Text" on page 63







## 5.22.3 Identification

*XML Tag:* Id

*Presence:* [1..1]

*Definition:* Natural person local identification and type.

The **Id** block contains the following elements (see datatype "[NaturalPersonIdentification1](#)" on page 27 for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		27
	IdentificationType	<IdTp>		[0..1]		28

## 5.22.4 Nationality

*XML Tag:* Ntlty

*Presence:* [0..1]

*Definition:* Nationality of the person.

*Datatype:* "CountryCode" on page 58







## 5.22.5 DateAndPlaceOfBirth

*XML Tag:* DtAndPlcOfBirth

*Presence:* [0..1]

*Definition:* Date on which and place at which a born person is born.







The **DtAndPlcOfBirth** block contains the following elements (see datatype "[DateAndPlaceOfBirth2](#)" on page 9 for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BirthDate	<BirthDt>		[1..1]		9
	ProvinceOfBirth	<PrvcOfBirth>		[0..1]		9
	CityOfBirth	<CityOfBirth>		[0..1]		9
	CountryOfBirth	<CtryOfBirth>		[0..1]		9

## 5.23 PartyIdentification246Choice

*Definition:* Identification of a party.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	LegalPerson	<LglPrsn>	{Or	[1..1]		37
	NaturalPerson	<NtrlPrsn>	Or}	[1..*]		37

Used in element(s)

"RightsHolder" on page 12







### 5.23.1 LegalPerson

*XML Tag:* LglPrsn

*Presence:* [1..1]

*Definition:* Legal entity.

The **LglPrsn** block contains the following elements (see datatype "[PartyIdentification269](#)" on page 40 for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NameAndAddress	<NmAndAdr>		[1..1]		40
	EmailAddress	<EmailAdr>		[0..1]		41
	Identification	<Id>		[0..1]		41
	CompanyRegisterShareholderIdentification	<CpnyRegrShrhldrId>		[0..1]		41
	CountryOfIncorporation	<CtryOfIncorprtn>		[0..1]		41







### 5.23.2 NaturalPerson

*XML Tag:* NtrlPrsn

*Presence:* [1..\*]

*Definition:* Private person.

The **NtrlPrsn** block contains the following elements (see datatype "[PartyIdentification250](#)" on page 38 for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NameAndAddress	<NmAndAdr>		[1..1]		38
	EmailAddress	<EmailAdr>		[0..1]		39
	Identification	<Id>		[0..1]		39
	Nationality	<Ntlty>		[0..1]		39
	DateAndPlaceOfBirth	<DtAndPlcOfBirth>		[0..1]		39
	CompanyRegisterShareholderIdentification	<CpnyRegrShrhldrId>		[0..1]		40

## 5.24 PartyIdentification250

*Definition:* Identification of a party.

❌ Removed - ❌ Partial Removed - ❖ Ignored - ❖ Partial Ignored - ⚠ Details below -   
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NameAndAddress	<NmAndAdr>		[1..1]		38
	EmailAddress	<EmailAdr>		[0..1]		39
	Identification	<Id>		[0..1]		39
	Nationality	<Ntlty>		[0..1]		39
	DateAndPlaceOfBirth	<DtAndPlcOfBirth>		[0..1]		39
	CompanyRegisterShareholderIdentification	<CpnyRegrShrhldrId>		[0..1]		40

**Used in element(s)**

"NaturalPerson" on page 37

### 5.24.1 NameAndAddress

*XML Tag:* NmAndAdr

*Presence:* [1..1]

*Definition:* Name and address of the party.

The **NmAndAdr** block contains the following elements (see datatype "PersonName3" on page 43 for details)

❌ Removed - ❌ Partial Removed - ❖ Ignored - ❖ Partial Ignored - ⚠ Details below -   
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NamePrefix	<NmPrfx>		[0..1]		43

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FirstName	<FrstNm>		[1..1]		43
	Surname	<SrnM>		[1..1]		43
	Address	<Adr>		[0..1]		43

## 5.24.2 EmailAddress

*XML Tag:* EmailAdr

*Presence:* [0..1]

*Definition:* Address for electronic mail (e-mail).

*Datatype:* "Max256Text" on page 63







## 5.24.3 Identification

*XML Tag:* Id

*Presence:* [0..1]

*Definition:* Natural person local identification and type.

The **Id** block contains the following elements (see datatype "NaturalPersonIdentification1" on page 27 for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		27
	IdentificationType	<IdTp>		[0..1]		28

## 5.24.4 Nationality

*XML Tag:* Ntlty

*Presence:* [0..1]

*Definition:* Nationality of the person.

*Datatype:* "CountryCode" on page 58







## 5.24.5 DateAndPlaceOfBirth

*XML Tag:* DtAndPlcOfBirth

*Presence:* [0..1]

*Definition:* Date on which and place at which a born person is born.

The **DtAndPlcOfBirth** block contains the following elements (see datatype "DateAndPlaceOfBirth2" on page 9 for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BirthDate	<BirthDt>		[1..1]		9
	ProvinceOfBirth	<PrvcOfBirth>		[0..1]		9
	CityOfBirth	<CityOfBirth>		[0..1]		9
	CountryOfBirth	<CtryOfBirth>		[0..1]		9

## 5.24.6 CompanyRegisterShareholderIdentification

*XML Tag:* CpnYRegrShrhldrId







*Presence:* [0..1]

*Definition:* Identification of the shareholder in the company share register.

*Datatype:* "Max35Text" on page 64

## 5.25 PartyIdentification269

*Definition:* Identification of a party.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NameAndAddress	<NmAndAdr>		[1..1]		40
	EmailAddress	<EmailAdr>		[0..1]		41
	Identification	<Id>		[0..1]		41
	CompanyRegisterShareholderIdentification	<CpnYRegrShrhldrId>		[0..1]		41
	CountryOfIncorporation	<CtryOfIncorprtn>		[0..1]		41

**Used in element(s)**

"LegalPerson" on page 37







### 5.25.1 NameAndAddress

*XML Tag:* NmAndAdr

*Presence:* [1..1]

*Definition:* Name and address of the party.

The **NmAndAdr** block contains the following elements (see datatype "PersonName2" on page 42 for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]



Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[1..1]		42
	Address	<Adr>		[0..1]		42

## 5.25.2 EmailAddress

*XML Tag:* EmailAdr

*Presence:* [0..1]

*Definition:* Address for electronic mail (e-mail).

*Datatype:* "Max256Text" on page 63







## 5.25.3 Identification

*XML Tag:* Id

*Presence:* [0..1]

*Definition:* Identification of the party.

The **Id** block contains the following elements (see datatype "[PartyIdentification198Choice](#)" on page 31 for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NationalRegistrationNumber	<NtlRegnNb>	{Or	[1..1]		31
	LEI	<LEI>	Or	[1..1]		31
	AnyBIC	<AnyBIC>	Or	[1..1]		31
	ClientIdentification	<ClntId>	Or	[1..1]		32
	ProprietaryIdentification	<PrtryId>	Or}	[1..1]		32

## 5.25.4 CompanyRegisterShareholderIdentification

*XML Tag:* CpnyRegrShrhldrId

*Presence:* [0..1]

*Definition:* Identification of the shareholder in the company share register.

*Datatype:* "Max35Text" on page 64

## 5.25.5 CountryOfIncorporation

*XML Tag:* CtryOfIncorprtn

*Presence:* [0..1]

*Definition:* Country in which the company is incorporated or legally registered.

*Datatype:* "CountryCode" on page 58

## 5.26 PersonName2

*Definition:* Identifies a person via its first name and surname.

🚫 Removed - 🚫 Partial Removed - ⬡ Ignored - ⬡ Partial Ignored - ⚠ Details below -  
**M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[1..1]		42
	Address	<Adr>		[0..1]		42

**Used in element(s)**

"NameAndAddress" on page 33, "NameAndAddress" on page 40

### 5.26.1 Name

*XML Tag:* Nm

*Presence:* [1..1]

*Definition:* First name(s) by which a natural person is known.

*Datatype:* "Max350Text" on page 63

### 5.26.2 Address

*XML Tag:* Adr

*Presence:* [0..1]

*Definition:* Postal address of the party.







The **Adr** block contains the following elements (see datatype "PostalAddress26" on page 46 for details)

🚫 Removed - 🚫 Partial Removed - ⬡ Ignored - ⬡ Partial Ignored - ⚠ Details below -  
**M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		47
	AddressLine	<AdrLine>		[0..5]		47
	StreetName	<StrtNm>		[0..1]		47
	BuildingNumber	<BldgNb>		[0..1]		47
	PostBox	<PstBx>		[0..1]		47
	PostCode	<PstCd>		[0..1]		48
	TownName	<TwnNm>		[0..1]		48
	CountrySubDivision	<CtrySubDvsn>		[0..1]		48
	Country	<Ctry>		[1..1]		48

## 5.27 PersonName3

*Definition:* Identifies a person via its first name and surname.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NamePrefix	<NmPrfx>		[0..1]		43
	FirstName	<FrstNm>		[1..1]		43
	Surname	<SrnM>		[1..1]		43
	Address	<Adr>		[0..1]		43

**Used in element(s)**

["NameAndAddress" on page 35](#), ["NameAndAddress" on page 38](#)

### 5.27.1 NamePrefix

*XML Tag:* NmPrfx

*Presence:* [0..1]

*Definition:* Prefix, as a title before a person's name.

*Datatype:* ["NamePrefix2Code" on page 70](#)

### 5.27.2 FirstName

*XML Tag:* FrstNm

*Presence:* [1..1]

*Definition:* First name(s) by which a natural person is known.

*Datatype:* ["Max350Text" on page 63](#)

### 5.27.3 Surname

*XML Tag:* SrnM

*Presence:* [1..1]

*Definition:* Name (s) by which a natural person is known and which is usually used to identify that party.

*Datatype:* ["Max350Text" on page 63](#)

### 5.27.4 Address

*XML Tag:* Adr

*Presence:* [0..1]

*Definition:* Postal address of the party.

The **Adr** block contains the following elements (see datatype ["PostalAddress26" on page 46](#) for details)

Removed - Partial Removed - Ignored - Partial Ignored - Details below -  
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		47
	AddressLine	<AdrLine>		[0..5]		47
	StreetName	<StrtNm>		[0..1]		47
	BuildingNumber	<BldgNb>		[0..1]		47
	PostBox	<PstBx>		[0..1]		47
	PostCode	<PstCd>		[0..1]		48
	TownName	<TwnNm>		[0..1]		48
	CountrySubDivision	<CtrySubDvsn>		[0..1]		48
	Country	<Ctry>		[1..1]		48

## 5.28 PostalAddress1

*Definition:* Information that locates and identifies a specific address, as defined by postal services.

Removed - Partial Removed - Ignored - Partial Ignored - Details below -  
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		44
	AddressLine	<AdrLine>		[0..5]		45
	StreetName	<StrtNm>		[0..1]		45
	BuildingNumber	<BldgNb>		[0..1]		45
	PostCode	<PstCd>		[0..1]		45
	TownName	<TwnNm>		[0..1]		46
	CountrySubDivision	<CtrySubDvsn>		[0..1]		46
	Country	<Ctry>		[1..1]		46

Used in element(s)

"Address" on page 26, "Location" on page 24

### 5.28.1 AddressType

*XML Tag:* AdrTp

*Presence:* [0..1]

*Definition:* Identifies the nature of the postal address.

*Datatype:* ["AddressType2Code" on page 57](#)

**Usage Guideline details**

- This element([seev.002.001.10/MeetingReference/Location/AddressType](#)) is removed.

## 5.28.2 AddressLine

*XML Tag:* AdrLine

*Presence:* [0..5]

*Definition:* Information that locates and identifies a specific address, as defined by postal services, that is presented in free format text.

*Datatype:* ["Max70Text" on page 65](#)

**Usage Guideline details**

- This element([seev.002.001.10/MeetingReference/Location/AddressLine](#)) is removed.

## 5.28.3 StreetName

*XML Tag:* StrtNm

*Presence:* [0..1]

*Definition:* Name of a street or thoroughfare.

*Datatype:* ["Max70Text" on page 65](#)

**Usage Guideline details**

- This element([seev.002.001.10/MeetingReference/Location/StreetName](#)) is removed.

## 5.28.4 BuildingNumber

*XML Tag:* BldgNb

*Presence:* [0..1]

*Definition:* Number that identifies the position of a building on a street.

*Datatype:* ["Max16Text" on page 62](#)

**Usage Guideline details**

- This element([seev.002.001.10/MeetingReference/Location/BuildingNumber](#)) is removed.

## 5.28.5 PostCode

*XML Tag:* PstCd

*Presence:* [0..1]

*Definition:* Identifier consisting of a group of letters and/or numbers that is added to a postal address to assist the sorting of mail.

*Datatype:* "Max16Text" on page 62

#### Usage Guideline details

- This element(seev.002.001.10/MeetingReference/Location/PostCode) is removed.

## 5.28.6 TownName

*XML Tag:* TwnNm

*Presence:* [0..1]

*Definition:* Name of a built-up area, with defined boundaries, and a local government.

*Datatype:* "Max35Text" on page 64

## 5.28.7 CountrySubDivision

*XML Tag:* CtrySubDvsn

*Presence:* [0..1]

*Definition:* Identifies a subdivision of a country for example, state, region, county.

*Datatype:* "Max35Text" on page 64

## 5.28.8 Country

*XML Tag:* Ctry







*Presence:* [1..1]

*Definition:* Nation with its own government.

*Datatype:* "CountryCode" on page 58

## 5.29 PostalAddress26

*Definition:* Information that locates and identifies a specific address, as defined by postal services.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		47
	AddressLine	<AdrLine>		[0..5]		47
	StreetName	<StrtNm>		[0..1]		47
	BuildingNumber	<BldgNb>		[0..1]		47
	PostBox	<PstBx>		[0..1]		47
	PostCode	<PstCd>		[0..1]		48

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	TownName	<TwnNm>		[0..1]		48
	CountrySubDivision	<CtrySubDvsn>		[0..1]		48
	Country	<Ctry>		[1..1]		48

**Used in element(s)**

"Address" on page 42, "Address" on page 43

## 5.29.1 AddressType

*XML Tag:* AdrTp

*Presence:* [0..1]

*Definition:* Identifies the nature of the postal address.

*Datatype:* "AddressType2Code" on page 57

## 5.29.2 AddressLine

*XML Tag:* AdrLine

*Presence:* [0..5]

*Definition:* Information that locates and identifies a specific address, as defined by postal services, that is presented in free format text.

*Datatype:* "Max70Text" on page 65

## 5.29.3 StreetName

*XML Tag:* StrtNm

*Presence:* [0..1]

*Definition:* Name of a street or thoroughfare.

*Datatype:* "Max70Text" on page 65

## 5.29.4 BuildingNumber

*XML Tag:* BldgNb

*Presence:* [0..1]

*Definition:* Number that identifies the position of a building on a street.

*Datatype:* "Max16Text" on page 62

## 5.29.5 PostBox

*XML Tag:* PstBx

*Presence:* [0..1]

*Definition:* Numbered box in a post office, assigned to a person or organisation, where letters are kept until called for.

Datatype: "Max16Text" on page 62

## 5.29.6 PostCode

XML Tag: PstCd

Presence: [0..1]

Definition: Identifier consisting of a group of letters and/or numbers that is added to a postal address to assist the sorting of mail.

Datatype: "Max16Text" on page 62

## 5.29.7 TownName

XML Tag: TwnNm

Presence: [0..1]

Definition: Name of a built-up area, with defined boundaries, and a local government.

Datatype: "Max35Text" on page 64

## 5.29.8 CountrySubDivision

XML Tag: CtrySubDvsn

Presence: [0..1]

Definition: Identifies a subdivision of a country for example, state, region, county.

Datatype: "Max35Text" on page 64

## 5.29.9 Country

XML Tag: Ctry

Presence: [1..1]

Definition: Nation with its own government.

Datatype: "CountryCode" on page 58

## 5.30 SafekeepingPlaceFormat42Choice

Definition: Choice of formats for a place of safekeeping.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -  
 📌 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>	{Or	[1..1]		49
	Country	<Ctry>	Or	[1..1]		49
	DigitalLedgerIdentification	<DgtlLdgrId>	Or	[1..1]		49
	TypeAndIdentification	<TpAndId>	Or	[1..1]		49
	Proprietary	<Prtry>	Or}	[1..1]		50



Used in element(s)

["SafekeepingPlace" on page 18](#)







## 5.30.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Place of safekeeping expressed as a code and a narrative description.

The **Id** block contains the following elements (see datatype ["SafekeepingPlaceTypeAndText6"](#) on page 51 for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	SafekeepingPlaceType	<SfkpgPlcTp>		[1..1]		51
	Identification	<Id>		[0..1]		51

## 5.30.2 Country

XML Tag: Ctry

Presence: [1..1]

Definition: Place of safekeeping expressed with a country code.

Datatype: ["CountryCode" on page 58](#)

## 5.30.3 DigitalLedgerIdentification

XML Tag: DgtlLdgrId

Presence: [1..1]

Definition: Place of safekeeping expressed with a Digital Ledger Identifier. It identifies a digital ledger or distributed ledger system (for example, blockchain or similar platforms).

Datatype: ["DTI2024Identifier" on page 59](#)







## 5.30.4 TypeAndIdentification

XML Tag: TpAndId

Presence: [1..1]

Definition: Place of safekeeping expressed with a type and identification.

The **TpAndId** block contains the following elements (see datatype ["SafekeepingPlaceTypeAndIdentification1"](#) on page 50 for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	SafekeepingPlaceType	<SfkpgPlcTp>		[1..1]		50
	Identification	<Id>		[1..1]		50







## 5.30.5 Proprietary

*XML Tag:* Prtry

*Presence:* [1..1]

*Definition:* Place of safekeeping expressed with a propriety identification scheme.







The **Prtry** block contains the following elements (see datatype "[GenericIdentification78](#)" on page 16 for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[1..1]		16
	Identification	<Id>		[0..1]		17

## 5.31 SafekeepingPlaceTypeAndIdentification1

*Definition:* Identification of the type of place of safekeeping expressed as a code and a BIC.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	SafekeepingPlaceType	<SfkpgPlcTp>		[1..1]		50
	Identification	<Id>		[1..1]		50

**Used in element(s)**

["TypeAndIdentification"](#) on page 49

### 5.31.1 SafekeepingPlaceType

*XML Tag:* SfkpgPlcTp

*Presence:* [1..1]

*Definition:* Place of safekeeping as a code.

*Datatype:* ["SafekeepingPlace1Code"](#) on page 71

### 5.31.2 Identification

*XML Tag:* Id







*Presence:* [1..1]

*Definition:* Place of safekeeping.

*Datatype:* ["AnyBICDec2014Identifier" on page 58](#)

## 5.32 SafekeepingPlaceTypeAndText6

*Definition:* Identification of the place of safekeeping expressed as a code and a narrative description.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	SafekeepingPlaceType	<SfkpgPlcTp>		[1..1]		51
	Identification	<Id>		[0..1]		51

**Used in element(s)**

["Identification" on page 49](#)

### 5.32.1 SafekeepingPlaceType

*XML Tag:* SfkpgPlcTp

*Presence:* [1..1]

*Definition:* Place of safekeeping as a code.

*Datatype:* ["SafekeepingPlace2Code" on page 72](#)

### 5.32.2 Identification

*XML Tag:* Id







*Presence:* [0..1]



*Definition:* Additional information about the place of safekeeping.

*Datatype:* ["Max35Text" on page 64](#)

## 5.33 SecurityIdentification19

*Definition:* Identification of a security.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ISIN	<ISIN>		[0..1]		52
	OtherIdentification	<OthrId>		[0..*]		53
	Description	<Desc>		[0..1]		53

**Rules****R8 DescriptionPresenceRule ✓**

If Description is not present then either ISIN or at least one occurrence of OtherIdentification must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00192
- *Error Text:* At least one identification must be present.

**R9 OtherIdentificationPresenceRule ✓**

If OtherIdentification is not present then either ISIN or Description must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00193
- *Error Text:* At least one identification must be present.

**R10 ISINPresenceRule ✓**

If ISIN is not present then either Description or at least one occurrence of OtherIdentification must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00194
- *Error Text:* At least one identification must be present.

**R11 DescriptionUsageRule**

Description must be used alone as the last resort.

Error handling: Undefined

**R12 ISINGuideline**

When an ISIN code exists, it is strongly recommended that the ISIN be used.

Error handling: Undefined

**Used in element(s)**

"FinancialInstrumentIdentification" on page 54

## 5.33.1 ISIN

*XML Tag:* ISIN

*Presence:* [0..1]

*Definition:* International Securities Identification Number (ISIN). A numbering system designed by the United Nation's International Organisation for Standardisation (ISO). The ISIN is composed of a 2-character prefix representing the country of issue, followed by the national security number (if one exists),

and a check digit. Each country has a national numbering agency that assigns ISIN numbers for securities in that country.

*Datatype:* ["ISINOct2015Identifier" on page 60](#)

#### Usage Guideline details

- This element([see v.002.001.10/Security/FinancialInstrumentIdentification/ISIN](#)) is removed.







## 5.33.2 OtherIdentification


*XML Tag:* OthrId

*Presence:* [0..\*]

*Definition:* Identification of a security by proprietary or domestic identification scheme.

The **OthrId** block contains the following elements (see datatype ["OtherIdentification1" on page 28](#) for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		28
	Suffix	<Sfx>		[0..1]		28
	Type	<Tp>		[1..1]		29

## 5.33.3 Description

*XML Tag:* Desc

*Presence:* [0..1]

*Definition:* Textual description of a security instrument.







*Datatype:* ["Max140Text" on page 62](#)


#### Usage Guideline details

- This element([see v.002.001.10/Security/FinancialInstrumentIdentification/Description](#)) is removed.

## 5.34 SecurityPosition23

*Definition:* Identification of a security and its balance.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstrumentIdentification	<FinInstrmId>		[1..1]		54
	Position	<Pos>		[0..1000]		54

Used in element(s)

"Security" on page 7







## 5.34.1 FinancialInstrumentIdentification



XML Tag: FinInstrmId

Presence: [1..1]

Definition: Identification of the security, as assigned under a formal or proprietary identification scheme.

The **FinInstrmId** block contains the following elements (see datatype "SecurityIdentification19" on page 51 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -   
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ISIN	<ISIN>		[0..1]		52
	OtherIdentification	<OthrId>		[0..*]		53
	Description	<Desc>		[0..1]		53







## 5.34.2 Position

XML Tag: Pos

Presence: [0..1000]

Definition: Amount of securities that are eligible for the vote.

The **Pos** block contains the following elements (see datatype "EligiblePosition21" on page 10 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -   
 Mandatory - R[x..x] Repeatability[details]







Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AccountIdentification	<AcctId>		[0..1]		11
	BlockChainAddressOrWallet	<BlckChainAdrOrWlt>		[0..1]		11
	AccountOwner	<AcctOwnr>		[0..1]		11
	HoldingBalance	<HldgBal>		[0..15]		12
	RightsHolder	<RghtsHldr>		[0..250]		12

## Usage Guideline details

- This element(seev.002.001.10/Security/Position) is removed.

## 5.35 SignedQuantityFormat14

*Definition:* Signed quantity of a security for various quantity formats.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ShortLongPosition	<ShrtLngPos>		[1..1]		55
	Quantity	<Qty>		[1..1]		55

Used in element(s)

"Balance" on page 17

### 5.35.1 ShortLongPosition

*XML Tag:* ShrtLngPos

*Presence:* [1..1]

*Definition:* Sign of the quantity of securities.

*Datatype:* "ShortLong1Code" on page 75







### 5.35.2 Quantity

*XML Tag:* Qty

*Presence:* [1..1]

*Definition:* Quantity of securities.







The **Qty** block contains the following elements (see datatype "FinancialInstrumentQuantity45Choice" on page 12 for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Unit	<Unit>	{Or	[1..1]		13
	FaceAmount	<FaceAmt>	Or	[1..1]		13
	DigitalTokenUnit	<DgtlTknUnit>	Or}	[1..1]		13

## 5.36 SupplementaryData1

*Definition:* Additional information that can not be captured in the structured fields and/or any other specific block.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	PlaceAndName	<PlcAndNm>		[0..1]		56
	Envelope	<Envlp>		[1..1]		56

## Rules

### R13 SupplementaryDataRule

This component may not be used without the explicit approval of a SEG and submission to the RA of ISO 20022 compliant structure(s) to be used in the Envelope element.

Error handling: Undefined

## Used in element(s)

["SupplementaryData" on page 8](#)

## 5.36.1 PlaceAndName

*XML Tag:* PlcAndNm

*Presence:* [0..1]

*Definition:* Unambiguous reference to the location where the supplementary data must be inserted in the message instance.

In the case of XML, this is expressed by a valid XPath.

*Datatype:* ["Max350Text" on page 63](#)

## 5.36.2 Envelope

*XML Tag:* Envlp

*Presence:* [1..1]

*Definition:* Technical element wrapping the supplementary data.



## 6 Message Datatypes

**Note** The following chapter identifies the datatypes that are used in the message.

### 6.1 AddressType2Code

*Definition:* Specifies the type of address.

*Type:* CodeSet

Code	Name	Definition
ADDR	Postal	Address is the complete postal address.
BIZZ	Business	Address is the business address.
DLVY	DeliveryTo	Address is the address to which delivery is to take place.
HOME	Residential	Address is the home address.
MLTO	MailTo	Address is the address to which mail is sent.
PBOX	POBox	Address is a postal office (PO) box.

**Used in element(s)**

["AddressType" on page 44](#), ["AddressType" on page 47](#)

**Restricts**

["AddressTypeCode" on page 57](#)

### 6.2 AddressTypeCode

*Definition:* Specifies the type of address.

*Type:* CodeSet

Code	Name	Definition
ADDR	Postal	Address is the complete postal address.
BIZZ	Business	Address is the business address.
DLVY	DeliveryTo	Address is the address to which delivery is to take place.
HOME	Residential	Address is the home address.
MLTO	MailTo	Address is the address to which mail is sent.
PBOX	POBox	Address is a postal office (PO) box.

**Is restricted by**

["AddressType2Code" on page 57](#)

## 6.3 AnyBICDec2014Identifier

*Definition:* Code allocated to a financial or non-financial institution by the ISO 9362 Registration Authority, as described in ISO 9362: 2014 - "Banking - Banking telecommunication messages - Business identifier code (BIC)".

*Type:* IdentifierSet

### Format

pattern [A-Z0-9]{4,4}[A-Z]{2,2}[A-Z0-9]{2,2}([A-Z0-9]{3,3}){0,1}

### Rules

#### R7 AnyBIC ✓

Only a valid Business identifier code is allowed. Business identifier codes for financial or non-financial institutions are registered and published by the ISO 9362 Registration Authority in the ISO directory of BICs, and consists of eight (8) or eleven (11) contiguous characters.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00008
- *Error Text:* Invalid BIC.

### Used in element(s)

"AnyBIC" on page 29, "AnyBIC" on page 31, "Identification" on page 50

## 6.4 CountryCode

*Definition:* Code to identify a country, a dependency, or another area of particular geopolitical interest, on the basis of country names obtained from the United Nations (ISO 3166, Alpha-2 code).

*Type:* CodeSet

### Format

pattern [A-Z]{2,2}

### Rules

#### R1 Country ✓

The code is checked against the list of country names obtained from the United Nations (ISO 3166, Alpha-2 code).

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00004
- *Error Text:* Invalid Country Code.

**Used in element(s)**

["Country" on page 46](#), ["Country" on page 48](#), ["Country" on page 49](#), ["CountryOfBirth" on page 9](#), ["CountryOfIncorporation" on page 41](#), ["Nationality" on page 36](#), ["Nationality" on page 39](#)

## 6.5 DTI2024Identifier

*Definition:* The Digital Token Identifier (DTI) is an 8 character code assigned to fungible digital assets which uses distributed ledger technology for its issuance, storage, exchange, record of ownership or transaction validation and is not a currency (ISO 4217) as described in ISO 24165 - DTI. A check character, using the same character set as the base number, shall be calculated and added.

*Type:* IdentifierSet

**Format**

pattern [1-9B-DF-HJ-NP-TV-XZ][0-9B-DF-HJ-NP-TV-XZ]{8,8}

**Used in element(s)**

["DigitalLedgerIdentification" on page 49](#)

## 6.6 DecimalNumber

*Definition:* Number of objects represented as a decimal number, for example 0.75 or 45.6.

*Type:* Quantity

**Format**

fractionDigits	17
totalDigits	18

**Used in element(s)**

["Unit" on page 13](#)

## 6.7 Exact4AlphaNumericText

*Definition:* Specifies an alphanumeric string with a length of 4 characters.

*Type:* Text

**Format**

pattern [a-zA-Z0-9]{4}

**Used in element(s)**

["Identification" on page 15](#)

## 6.8 ExternalFinancialInstrument-IdentificationType1Code

*Definition:* Specifies the external financial instrument identification type scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from [www.iso20022.org](http://www.iso20022.org).

*Type:* CodeSet

**Format**

maxLength	4
minLength	1

**Used in element(s)**

"Code" on page 19

**Restricts**

"ExternalFinancialInstrumentIdentificationTypeCode" on page 60

## 6.9 ExternalFinancialInstrument-IdentificationTypeCode

*Definition:* Specifies the external financial instrument identification type scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from [www.iso20022.org](http://www.iso20022.org).

*Type:* CodeSet

**Format**

maxLength	4
minLength	1

**Is restricted by**

"ExternalFinancialInstrumentIdentificationType1Code" on page 59

## 6.10 ISINOct2015Identifier

*Definition:* The International Securities Identification Number is a code allocated to financial instruments as well as referential instruments, as described in the ISO 6166 standard, associated with the minimum descriptive data. The ISIN consists of a prefix using the alpha-2 country codes or reserved codes specified in ISO 3166 or other prefixes as may be determined by the Registration Authority for the ISO 6166 standard, a nine characters (alphanumeric) basic code and a check digit.

Note: this identifier also supports the new version of the standard, which was published in 2021 (ISO 6166:2021) as there is no update in the pattern.

Type: IdentifierSet

**Format**

pattern [A-Z]{2,2}[A-Z0-9]{9,9}[0-9]{1,1}

**Used in element(s)**

"ISIN" on page 52

## 6.11 ISODate

*Definition:* A particular point in the progression of time in a calendar year expressed in the YYYY-MM-DD format. This representation is defined in "XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004" which is aligned with ISO 8601.

Type: Date

**Used in element(s)**

"BirthDate" on page 9, "Date" on page 18

## 6.12 ISODateTime

*Definition:* A particular point in the progression of time defined by a mandatory date and a mandatory time component, expressed in either UTC time format (YYYY-MM-DDThh:mm:ss.sssZ), local time with UTC offset format (YYYY-MM-DDThh:mm:ss.sss+/-hh:mm), or local time format (YYYY-MM-DDThh:mm:ss.sss). These representations are defined in "XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004" which is aligned with ISO 8601.

Note on the time format:

1) beginning / end of calendar day

00:00:00 = the beginning of a calendar day

24:00:00 = the end of a calendar day

2) fractions of second in time format

Decimal fractions of seconds may be included. In this case, the involved parties shall agree on the maximum number of digits that are allowed.

Type: DateTime

**Used in element(s)**

"MeetingDateAndTime" on page 23

## 6.13 ImpliedCurrencyAndAmount

*Definition:* Number of monetary units specified in a currency where the unit of currency is implied by the context and compliant with ISO 4217. The decimal separator is a dot.

Note: a zero amount is considered a positive amount.

*Type:* Amount

**Format**

fractionDigits	5
minInclusive	0
totalDigits	18

**Used in element(s)**

"FaceAmount" on page 13

## 6.14 LEIdentifier

*Definition:* Legal Entity Identifier is a code allocated to a party as described in ISO 17442 "Financial Services - Legal Entity Identifier (LEI)".

*Type:* IdentifierSet

**Format**

pattern	[A-Z0-9]{18,18}[0-9]{2,2}
---------	---------------------------

**Used in element(s)**

"LEI" on page 31, "LEI" on page 31

## 6.15 Max140Text

*Definition:* Specifies a character string with a maximum length of 140 characters.

*Type:* Text

**Format**

maxLength	140
minLength	1

**Used in element(s)**

"BlockchainAddressOrWallet" on page 11, "CancellationReason" on page 22, "Description" on page 53

## 6.16 Max16Text

*Definition:* Specifies a character string with a maximum length of 16 characters.

*Type:* Text

**Format**

maxLength	16
minLength	1

**Used in element(s)**

["BuildingNumber" on page 45](#), ["BuildingNumber" on page 47](#), ["PostBox" on page 47](#), ["PostCode" on page 45](#), ["PostCode" on page 48](#), ["Suffix" on page 28](#)

## 6.17 Max256Text

*Definition:* Specifies a character string with a maximum length of 256 characters.

*Type:* Text

**Format**

maxLength	256
minLength	1

**Used in element(s)**

["EmailAddress" on page 33](#), ["EmailAddress" on page 35](#), ["EmailAddress" on page 39](#), ["EmailAddress" on page 41](#)

## 6.18 Max30DecimalNumber

*Definition:* Number of objects represented as a decimal number, for example 0.75 or 45.6 with a maximum of 30 digits and 29 fraction digits.

*Type:* Quantity

**Format**

fractionDigits	29
totalDigits	30

**Used in element(s)**

["DigitalTokenUnit" on page 13](#)

## 6.19 Max350Text

*Definition:* Specifies a character string with a maximum length of 350 characters.

*Type:* Text

**Format**

maxLength	350
minLength	1

**Used in element(s)**

["FirstName" on page 43](#), ["Name" on page 26](#), ["Name" on page 42](#), ["PlaceAndName" on page 56](#), ["Surname" on page 43](#)

## 6.20 Max35Text

*Definition:* Specifies a character string with a maximum length of 35 characters.

*Type:* Text

### Format

maxLength	35
minLength	1

### Used in element(s)

"AccountIdentification" on page 11, "CityOfBirth" on page 9, "CompanyRegisterShareholderIdentification" on page 40, "CompanyRegisterShareholderIdentification" on page 41, "CountrySubDivision" on page 46, "CountrySubDivision" on page 48, "Identification" on page 15, "Identification" on page 17, "Identification" on page 27, "Identification" on page 28, "Identification" on page 51, "Issuer" on page 14, "Issuer" on page 15, "Issuer" on page 16, "IssuerMeetingIdentification" on page 23, "MeetingIdentification" on page 22, "NationalRegistrationNumber" on page 31, "Proprietary" on page 19, "Province-Of-Birth" on page 9, "SchemeName" on page 14, "SchemeName" on page 15, "SchemeName" on page 16, "TownName" on page 46, "TownName" on page 48

## 6.21 Max4AlphaNumericText

*Definition:* Specifies an alphanumeric string with a maximum length of 4 characters.

*Type:* Text

### Format

maxLength	4
minLength	1
pattern	[a-zA-Z0-9]{1,4}

### Used in element(s)

"Identification" on page 14

## 6.22 Max50Text

*Definition:* Specifies a character string with a maximum length of 50 characters.

*Type:* Text

### Format

maxLength	50
minLength	1

### Used in element(s)

"ClientIdentification" on page 32



## 6.23 Max70Text

*Definition:* Specifies a character string with a maximum length of 70characters.

*Type:* Text

### Format

maxLength	70
minLength	1

### Used in element(s)

"AddressLine" on page 45, "AddressLine" on page 47, "StreetName" on page 45, "StreetName" on page 47

## 6.24 MeetingCancellationReason2Code

*Definition:* Specifies the reason for cancelling a meeting.

*Type:* CodeSet

Code	Name	Definition
PROC	Processing	<p>Cancellation due to a processing error.</p> <p><b>Usage Guideline restrictions for this code</b></p> <ul style="list-style-type: none"> <li>• on seev.002.001.10/Reason/CancellationReason-Code/Code/Processing</li> </ul> <p><b>Synonym (DTCC):</b> DTC Event Status (Deleted)</p>
QORM	Quorum	<p>Cancellation due to insufficient participation to the vote.</p> <p><b>Usage Guideline restrictions for this code</b></p> <ul style="list-style-type: none"> <li>• This code(seev.002.001.10/Reason/CancellationReason-Code/Code/Quorum) is removed.</li> </ul>

Code	Name	Definition
WITH	Withdrawal	<p>Cancellation due to the meeting being cancelled by the issuer.</p> <p><b>Usage Guideline restrictions for this code</b></p> <ul style="list-style-type: none"> <li>• on seev.002.001.10/Reason/CancellationReason-Code/Code/Withdrawal</li> </ul> <p><b>Synonym (DTCC):</b> DTC Event Status (Canceled)</p>

**Used in element(s)**

"Code" on page 20

**Restricts**

"MeetingCancellationReasonCode" on page 66

## 6.25 MeetingCancellationReasonCode

*Definition:* Specifies the reason for cancelling a meeting.

*Type:* CodeSet

Code	Name	Definition
OTHR	Other	Cancellation due to another reason.
PROC	Processing	Cancellation due to a processing error.
QORM	Quorum	Cancellation due to insufficient participation to the vote.
WITH	Withdrawal	Cancellation due to the meeting being cancelled by the issuer.

**Is restricted by**

"MeetingCancellationReason2Code" on page 65

## 6.26 MeetingType4Code

*Definition:* Specifies a type of security holders meeting.

*Type:* CodeSet

Code	Name	Definition
BMET	BondHolderMeeting	Physical meeting of bond holders.

Code	Name	Definition
		<p><b>Usage Guideline restrictions for this code</b></p> <ul style="list-style-type: none"> <li>• This code(seev.002.001.10/MeetingReference/Type/BondHolder-Meeting) is removed.</li> </ul>
CMET	CourtMeeting	<p>Meeting is the result of a legal proceeding.</p> <p><b>Usage Guideline restrictions for this code</b></p> <ul style="list-style-type: none"> <li>• This code(seev.002.001.10/MeetingReference/Type/CourtMeeting) is removed.</li> </ul>
GMET	General	Includes annual and ordinary meetings. Statutory meeting(s) usually held at least once a year. The resolutions are related to the usual business of the company, for example, approval of dividends and directors. These meetings are always issuer initiated.
MIXD	Mixed	<p>Meeting which contains both ordinary and extraordinary resolutions.</p> <p><b>Usage Guideline restrictions for this code</b></p> <ul style="list-style-type: none"> <li>• This code(seev.002.001.10/MeetingReference/Type/Mixed) is removed.</li> </ul>
SPCL	Special	Meeting that takes place as needed that is neither ordinary nor extraordinary.
XMET	Extraordinary	Meeting that takes place as needed, in addition to the general meetings, is extraordinary as per the bylaws. The resolutions are related to the unusual business of the company, for example, approval of takeovers or mergers or spin-offs. These meetings are always issuer initiated.

**Used in element(s)**

"Type" on page 23

**Restricts**

"MeetingTypeV2Code" on page 69

## 6.27 MeetingTypeClassification2Code

*Definition:* Classifies the meeting type.

*Type:* CodeSet

Code	Name	Definition
AMET	Annual	Meeting held periodically to approve the financial statements and to elect the board members and the auditors.
CLAS	Class	<p>Meeting for holders of a specific type of asset, for example, preferred shares, bonds.</p> <p><b>Usage Guideline restrictions for this code</b></p> <ul style="list-style-type: none"> <li>• This code(seev.002.001.10/MeetingReference/Classification/Code/Class) is removed.</li> </ul>
ISSU	IssuerInitiated	<p>Meeting is the result of an obligation or a decision made by the issuer as opposed to voting rights holder initiated, for example, contested meeting.</p> <p><b>Usage Guideline restrictions for this code</b></p> <ul style="list-style-type: none"> <li>• This code(seev.002.001.10/MeetingReference/Classification/Code/IssuerInitiated) is removed.</li> </ul>
OMET	Ordinary	<p>Meeting which is planned in the by-laws.</p> <p><b>Usage Guideline restrictions for this code</b></p> <ul style="list-style-type: none"> <li>• This code(seev.002.001.10/MeetingReference/Classification/Code/Ordinary) is removed.</li> </ul>

Code	Name	Definition
VRHI	VotingRightsHolderInitiated	<p>Meeting is the result of a request or an action of a voting right holder(s), for example, contested meeting.</p> <p><b>Usage Guideline restrictions for this code</b></p> <ul style="list-style-type: none"> <li>• This code(seev.002.001.10/MeetingReference/Classification/Code/VotingRightsHolderInitiated) is removed.</li> </ul>

**Used in element(s)**

"Code" on page 25

**Restricts**

"MeetingTypeClassificationCode" on page 69

## 6.28 MeetingTypeClassificationCode

*Definition:* Classifies the meeting type.

*Type:* CodeSet

Code	Name	Definition
AMET	Annual	Meeting held periodically to approve the financial statements and to elect the board members and the auditors.
CLAS	Class	Meeting for holders of a specific type of asset, for example, preferred shares, bonds.
CORT	Court	Specifies that the meeting is the result of a legal proceeding.
ISSU	IssuerInitiated	Meeting is the result of an obligation or a decision made by the issuer as opposed to voting rights holder initiated, for example, contested meeting.
OMET	Ordinary	Meeting which is planned in the by-laws.
VRHI	VotingRightsHolderInitiated	Meeting is the result of a request or an action of a voting right holder(s), for example, contested meeting.

**Is restricted by**

"MeetingTypeClassification2Code" on page 68

## 6.29 MeetingTypeV2Code

*Definition:* Specifies the type of security holders meeting.

Type: CodeSet

Code	Name	Definition
AMET	AnnualGeneralMeeting	Specifies a meeting held periodically to approve the financial statements and elect the board members and the auditors.
BMET	BondHolderMeeting	Physical meeting of bond holders.
CLAS	ClassMeeting	Meeting for a class of assets.
CMET	CourtMeeting	Meeting is the result of a legal proceeding.
GMET	General	Includes annual and ordinary meetings. Statutory meeting(s) usually held at least once a year. The resolutions are related to the usual business of the company, for example, approval of dividends and directors. These meetings are always issuer initiated.
MIXD	Mixed	Meeting which contains both ordinary and extraordinary resolutions.
OMET	Ordinary	Specifies a meeting that is not planned in the by laws.
SPCL	Special	Meeting that takes place as needed that is neither ordinary nor extraordinary.
XMET	Extraordinary	Meeting that takes place as needed, in addition to the general meetings, is extraordinary as per the bylaws. The resolutions are related to the unusual business of the company, for example, approval of takeovers or mergers or spin-offs. These meetings are always issuer initiated.

Is restricted by

"MeetingType4Code" on page 66

## 6.30 NamePrefix2Code

*Definition:* Specifies the terms used to formally address a person.

Type: CodeSet

Code	Name	Definition
DOCT	Doctor	Title of the person is Doctor or Dr.
MADM	Madam	Title of the person is Madam.
MIKS	GenderNeutral	Title of the person is gender neutral (Mx).
MISS	Miss	Title of the person is Miss.
MIST	Mister	Title of the person is Mister or Mr.

**Used in element(s)**

["NamePrefix" on page 43](#)

**Restricts**

["NamePrefixCode" on page 71](#)

## 6.31 NamePrefixCode

*Definition:* Specifies the terms used to formally address a person.

*Type:* CodeSet

Code	Name	Definition
DOCT	Doctor	Title of the person is Doctor or Dr.
MADM	Madam	Title of the person is Madam.
MIKS	GenderNeutral	Title of the person is gender neutral (Mx).
MISS	Miss	Title of the person is Miss.
MIST	Mister	Title of the person is Mister or Mr.

**Is restricted by**

["NamePrefix2Code" on page 70](#)

## 6.32 SafekeepingPlace1Code

*Definition:* Specifies the type of place of safekeeping.

*Type:* CodeSet

Code	Name	Definition
CUST	SharesHeldAtLocalCustodian	Financial instruments held at a local custodian.
ICSD	SharesHeldAtICSD	Financial instruments held at an International Central Securities Depository.
NCSD	SharesHeldAtNCSD	Financial instruments held at a National Central Securities Depository.
SHHE	SharesHeldElsewhere	Used for certain financial instruments, for example, US mutual funds, where settlement is internal only, that is, there is no external movement of securities.

**Used in element(s)**

["SafekeepingPlaceType" on page 50](#)

**Restricts**

["SafekeepingPlaceCode" on page 72](#)

## 6.33 SafekeepingPlace2Code

*Definition:* Specifies the type of place of safekeeping.

*Type:* CodeSet

Code	Name	Definition
ALLP	AllPlaces	All places of safekeeping where the financial instrument is held.
SHHE	SharesHeldElsewhere	Used for certain financial instruments, for example, US mutual funds, where settlement is internal only, that is, there is no external movement of securities.

**Used in element(s)**

"SafekeepingPlaceType" on page 51

**Restricts**

"SafekeepingPlaceCode" on page 72

## 6.34 SafekeepingPlaceCode

*Definition:* Specifies the type of place of safekeeping.

*Type:* CodeSet

Code	Name	Definition
ALLP	AllPlaces	All places of safekeeping where the financial instrument is held.
CUST	SharesHeldAtLocalCustodian	Financial instruments held at a local custodian.
ICSD	SharesHeldAtICSD	Financial instruments held at an International Central Securities Depository.
NCSD	SharesHeldAtNCSD	Financial instruments held at a National Central Securities Depository.
SHHE	SharesHeldElsewhere	Used for certain financial instruments, for example, US mutual funds, where settlement is internal only, that is, there is no external movement of securities.

**Is restricted by**

"SafekeepingPlace1Code" on page 71, "SafekeepingPlace2Code" on page 72

## 6.35 SecuritiesEntryType2Code

*Definition:* Specifies the type of securities entry on an account.

*Type:* CodeSet



Code	Name	Definition
BLOK	Blocked	Balance of securities that are blocked or frozen. A financial instrument may be unavailable due to external circumstances such as a court order, death of beneficiary or account owner, or bankruptcy.
BORR	Borrowed	Balance of securities that have been borrowed from another party.
COLI	CollateralIn	Balance of securities that belong to a third party and that are held for the purpose of collateralisation.
COLO	CollateralOut	Balance of securities that belong to the safekeeping account indicated within this message, and are deposited with a third party for the purpose of collateralisation.
ELIG	Eligible	Total number of securities eligible for this event.
INBA	InstructedBalance	Balance of instructed position.
LOAN	OnLoan	Balance of securities that have been loaned to a third party.
NOMI	Registered	Balance of securities that are registered (in the name of a nominee or of the beneficial owner).
PEND	PendingDelivery	Balance of securities that are pending delivery.
PENR	PendingReceipt	Balance of securities that are pending receipt.
REGO	OutForRegistration	Balance of securities currently being processed by the institution responsible for registering the new beneficial owner (or nominee) of securities after a transaction has settled.
SETD	Settled	Balance of securities representing only settled transactions.
SPOS	StreetPosition	Balance of securities that remain registered in the name of the prior beneficial owner of securities.
TRAD	Traded	Balance of securities representing traded transactions.
UNBA	UninstructedBalance	Balance of uninstructed position.

**Used in element(s)**

["BalanceType" on page 18](#)

**Restricts**

["SecuritiesEntryTypeCode" on page 73](#)

## 6.36 SecuritiesEntryTypeCode

*Definition:* Specifies the type of securities entry on an account.

*Type:* CodeSet

Code	Name	Definition
BLOK	Blocked	Balance of securities that are blocked or frozen. A financial instrument may be unavailable due to external circumstances such as a court order, death of beneficiary or account owner, or bankruptcy.
BORR	Borrowed	Balance of securities that have been borrowed from another party.
BTRA	BeingTransferred	Financial instrument is unavailable as a result of a transfer order, pending movement in the shareholders' register.
COLI	CollateralIn	Balance of securities that belong to a third party and that are held for the purpose of collateralisation.
COLO	CollateralOut	Balance of securities that belong to the safekeeping account indicated within this message, and are deposited with a third party for the purpose of collateralisation.
ELIG	Eligible	Total number of securities eligible for this event.
INBA	InstructedBalance	Balance of instructed position.
LOAN	OnLoan	Balance of securities that have been loaned to a third party.
NOMI	Registered	Balance of securities that are registered (in the name of a nominee or of the beneficial owner).
OTHR	Unclassified	Balance of securities that is unclassified, ie, is not identified with one of the existing sub-balance types.
PEND	PendingDelivery	Balance of securities that are pending delivery.
PENR	PendingReceipt	Balance of securities that are pending receipt.
PLED	Pledged	Balance of securities that are pledged, for example, a financial instrument is unavailable because it has been used or given as a guarantee.
REGO	OutForRegistration	Balance of securities currently being processed by the institution responsible for registering the new beneficial owner (or nominee) of securities after a transaction has settled.
SETD	Settled	Balance of securities representing only settled transactions.
SETT	SettlementPosition	Balance of securities representing only settled transactions; pending transactions not included.

Code	Name	Definition
SPOS	StreetPosition	Balance of securities that remain registered in the name of the prior beneficial owner of securities.
TRAD	Traded	Balance of securities representing traded transactions.
TRAN	InTransshipment	Balance of physical securities that are in transshipment, eg, in the process of being transferred from one depository or agent to another.
UNBA	UninstructedBalance	Balance of uninstructed position.
UNRG	Unregistered	Balance of securities that could not be registered due to foreign ownership limitation.
WDOC	WaitingDocumentation	Financial instrument is unavailable due to missing or incomplete documentation pertaining to the account, or due to a missing or incomplete order.

Is restricted by

"SecuritiesEntryType2Code" on page 72

## 6.37 ShortLong1Code

*Definition:* Specifies whether the securities position is short or long, that is, whether the balance is a negative or positive balance.

*Type:* CodeSet

Code	Name	Definition
LONG	Long	Position is long, that is, the balance is positive.
SHOR	Short	Position is short, that is, the balance is negative.

Used in element(s)

"ShortLongPosition" on page 55

Restricts

"ShortLongCode" on page 75

## 6.38 ShortLongCode

*Definition:* Specifies whether the securities position is short or long, that is, whether the balance is a negative or positive balance.

*Type:* CodeSet

Code	Name	Definition
LONG	Long	Position is long, that is, the balance is positive.
SHOR	Short	Position is short, that is, the balance is negative.

**Is restricted by**

"ShortLong1Code" on page 75

## 6.39 TypeOfIdentification4Code

*Definition:* Specifies the type of alternate identification which can be used to give an alternate identification of the party identified.

*Type:* CodeSet

Code	Name	Definition
ARNU	AlienRegistrationNumber	Number assigned by a government agency to identify foreign nationals.
CCPT	PassportNumber	Number assigned by a passport authority.
CORP	CorporateIdentification	Number assigned to a corporate entity.
CUST	Concat	Number assigned by an issuer to identify a customer via the concatenation of the birthdate and characters of the first name and surname.
DRLC	DriverLicenseNumber	Number assigned to a driver's license.
IDCD	IdentityCardNumber	Number assigned by a national authority to an identity card.
NRIN	NationalRegistrationIdentificationNumber	National registration identification number. In Singapore this is known as the NRIC.
SOCS	SocialSecurityNumber	Number assigned by a social security agency.
TXID	TaxIdentificationNumber	Number assigned by a tax authority to an entity.

**Used in element(s)**

"Code" on page 19

**Restricts**

"TypeOfIdentificationCode" on page 76

## 6.40 TypeOfIdentificationCode

*Definition:* Specifies the type of alternate identification which can be used to give an alternate identification of the party identified.

*Type:* CodeSet

Code	Name	Definition
ARNU	AlienRegistrationNumber	Number assigned by a government agency to identify foreign nationals.
CCPT	PassportNumber	Number assigned by a passport authority.
CHTY	TaxExemptIdentificationNumber	Number assigned to a tax exempt entity.
CORP	CorporateIdentification	Number assigned to a corporate entity.
CUST	Concat	Number assigned by an issuer to identify a customer via the concatenation of the birthdate and characters of the first name and surname.
DRLC	DriverLicenseNumber	Number assigned to a driver's license.
FIIN	ForeignInvestmentIdentityNumber	Number assigned to a foreign investor (other than the alien number).
IDCD	IdentityCardNumber	Number assigned by a national authority to an identity card.
NRIN	NationalRegistrationIdentificationNumber	National registration identification number. In Singapore this is known as the NRIC.
SOCS	SocialSecurityNumber	Number assigned by a social security agency.
TXID	TaxIdentificationNumber	Number assigned by a tax authority to an entity.

**Is restricted by**

"TypeOfIdentification4Code" on page 76

# Legal Notices

## Copyright

SWIFT © 2025. All rights reserved.

This material is a component of MyStandards, the SWIFT collaborative Web application used to manage standards definitions and industry usage. It can only be used and distributed in accordance with MyStandards Terms of Use.

Unless otherwise agreed in writing with SWIFT SCRL, you have no right to:

- authorise external end users to use this component for other purposes than their internal use.
- remove, alter, cover, obfuscate or cancel from view any copyright or other proprietary rights notices appearing in this physical medium.
- re-sell or authorise another party e.g. software and service providers, to re-sell this component.

## Confidentiality

This publication may contain SWIFT or third-party confidential information. Only disclose it outside your organisation in accordance with MyStandards Terms of Use and your related license rights.

This component is provided 'AS IS'. SWIFT does not give and excludes any express or implied warranties with respect to this component such as but not limited to any guarantee as to its quality, supply or availability.

Any and all rights, including title, ownership rights, copyright, trademark, patents, and any other intellectual property rights of whatever nature in this component will remain the exclusive property of SWIFT or its licensors.

## Trademarks and Patents

SWIFT is the trade name of S.W.I.F.T. SCRL. The following are registered trademarks of SWIFT: SWIFT, the SWIFT logo, 3SKey, Innotribe, Sibos, SWIFTNet, MyStandards, SWIFTReady, and Accord. Other product, service, or company names in this publication are trade names, trademarks, or registered trademarks of their respective owners.